




## Technical Data sonnenBatterie eco 8.0

	eco 8.0/5	eco 8.0/7.5	eco 8.0/10	eco 8.0/12.5	eco 8.0/15	
Nominal battery capacity in kWh	5.0	7.5	10.0	12.5	15.0	
Depth of discharge (DoD)	90%					
Cell technology	LFP (Lithium Iron Phosphate)					
Cabinet option 1 (5.0 kWh)						
Weight in kg	81	_	-	_	-	
Dimensions (H/W/D) in cm	88/67/23	-	-	-	-	
Cabinet option 2 (5.0 kWh - 10.0 k	kWh)¹					
Weight in kg	97	120	143	_	_	
Dimensions (H/W/D) in cm	137/67/23	137/67/23	137/67/23	-	-	
Cabinet option 3 (5.0kWh-15.0k	«Wh)¹					
Weight in kg	108	131	154	177	200	
Dimensions (H/W/D) in cm	186/67/23	186/67/23	186/67/23	186/67/23	186/67/23	
Nominal power (charging/discharging) in kW	2.5	3.3	3.3	3.3	3.3	
Max. inverter efficiency	96%					
Max. battery efficiency	98%					
Ambient temperature range	-5°C − +45°C²					
Dust and water protection	IP30					





## Technical Data sonnenBatterie eco 8.0

	eco 8.0/5	eco 8.0/7.5	eco 8.0/10	eco 8.0/12.5	eco 8.0/15
Operating mode			three phase		
Tests and directives	SGS TÜV Saar, UN 38.3, IEC 62133, IEC 62040-1, AS/NZS 4777.2, IEC 62619				
Battery service life	designed for 20 years				
Warranty	10 years³				
Cvcles	10.000³				

## Available options

Multi-Touch-Display	7 inches
sonnenBackup-Box	emergency backup
sonnenWallmount	installation mount

We reserve the right to make technical changes and updates without prior notice. Specific values, performance data and other information in this data sheet, brochures and other product information, as well as illustrations and drawings in these documents, are solely illustrative and are subject to ongoing revision and modification. We do not warrant the accuracy or completeness of any information in these documents unless otherwise explicitly stated. Only the information in order confirmation documents or purchase contracts is binding.

<sup>&</sup>lt;sup>1</sup> There are two cabinet versions available. By default, the large cabinet is included (Dimensions H/W/D 98/67/23). If a small cabinet is needed for a storage battery of 5.0 kWh up to 10.0 kWh, this must be specified when ordering. <sup>2</sup> Derating at approx. 35 °C. <sup>3</sup> Warranty on all parts. To learn more about our current warranty terms and conditions, please visit sonnenbatterie.de/en/terms-and-conditions or call our customer hotline and request a copy. Standard housing color: white. Housing color black only on request.